



AROPEX TILESTYLE

UV Resistant Tile coat

Apollo's "AropeX Tile style UV- resistant tile coat "is a high performance paint formulated with a special grade of acrylic emulsion with light, fast pigments, unique additives like anti-fungal properties and unique organo-silicone chemistry which imparts visible water repellency . This ensures long term protection of the roof tiles and preserves its rich new look.

USP:- Strong Water repellence: It Has excellent water repellency property and provides excellent resistance against algal and fungal growth, **Adhesion :**The Tile Styles film has better adhesion on tiles, crack bridging abilities and a tough film,

and **Long Lasting:** Tile styles incorporates the latest state of the art technology to provide long lasting performance in the most tropical and harsh conditions.

Usage area: On Roof tiles.

DIRECTIONS FOR USE:

Cleaning: Ensure that the surface to be painted is free from any loose paint, dust grease or from any dampness or seepage. Any previous growth of fungus, algae or moss needs to be removed thoroughly by using Apollo's Cleanex solution or vigorous wire brushing and cleaning with water.

Please Note: Use of any kind of Putty or Primer is NOT recommended.

Topcoat: Apply 2-3 coats by diluting 1 litre of AropeX Tile style with 300ml of water. A gap of 4-6 hours should be given between coats. This product is NOT recommended for use on glazed, non –porous or very smooth tiles.

Maintenance Tips: For the best performance of the paint ensure proper washing and cleaning of all algal and fungal growth at regular intervals of six months.

COVERAGE *

Roof Tiles	No of coats	Coverage
By brush application	2 coats	50-60 sq ft/ltr

**It depends on many factors like surface conditions, surface preparation, application skill, weather conditions, dilution etc. the coverage mentioned is under ideal conditions and will vary depending on site conditions.

Please apply Tile style either early morning or late in the evening, avoiding hot tiles due to sunlight, so that you get recommended Coverage.

TECHNICAL DATA:

1	Thinning	Potable Water	7	Flash Point	100% water –base paint, hence NA
2	Thinning Ratio	Maximum of 300ml of water per 1ltr of Paint.	8	Recommended Surface	On Roof Tiles
3	Method of application	Brush	9	Certification	As per IS 15489:2004
4	Drying Time	SD :30minutes	10	Fire Hazard Class	Non - flammable
5	Pot life of thinned material	Use within 24hrs	11	Safety Data	Refer MSDS
6	Gloss Level	3-12 @60° GH	12	VOC (gm/ltr)	30.0gm/ltr

POINTS TO NOTE :

- Shake well before use and do not over dilute.
- Please keep out of reach of children and away from foodstuff.
- In case of contact with eyes, wash immediately with water and seek medical advice.
- Keep the container tightly closed to prevent drying.
- Do not pour leftover paint down the drain or in water courses.

SPECIAL NOTE *

Before painting the following things should be checked thoroughly.

- pH value of the wall surface (Ideal condition between 7-10).
- Moisture content of the wall (Ideal condition –below 10-12%).
- If these are violated, owner will be responsible.*As per test conducted at Apollo R&D.

Version: APPL/01/2017.