



BRITE CEILING WHITE

Light Dispersion Emulsion

New Generation Paint for CEILING with high light dispersions.

Apollo's BRITE CEILING WHITE Light Dispersion Emulsion is a new generation Paint Specially Formulated for Ceilings with high light dispersion properties which helps to provides bright ceilings and hides undulations.

USP: Supreme White Ceilings, Hides Undulations, and Highlights Interiors.

Usage area: CEILING Surfaces.

DIRECTIONS FOR USE:

Surface Preparation: For New Surfaces ensure the plaster is completely dry and thoroughly clean, free from any dust, flakes, and grease etc., Ensure that all water leakages/ seepages are repaired before painting. For previously painted surface; remove all loose particles, powdery material or defective paint by thorough wire brushing, scraping and water jetting, if required.

Filling:

- a).For CRACKS: For filling cracks up to 3mm use Apollo's INSTACARE CRACK LOCK.
- b).For HOLES & DENTS: In case of dents and holes use Apollo's Wall grace putty or white cement and fine sand in the ratio 1:3.

Recommended Undercoats:

Option 1: For best performance, it is recommended to apply Brite Ceiling white as self priming with a thinning ratio of one part of paint with one part of water.

Option 2: Apply one coat of Apollo's " Instacare Seal O Prime High Performance Primer Sealer Interior & Exterior(Silicon Enriched) as primer coat with a thinning ratio of one part of primer with one part of water.

Option 3: Apply one coat of Apollo's Aroprime Interior WT Primer with a thinning ratio of 1ltr of primer With 750ml water.

Top Coat: Apply 2 coats by diluting 1 litre of Apollo's Brite Ceiling White with maximum 200-350ml of water. A gap of 4-6 hours should be given between coats. It can be applied by brush or roller or conventional /airless spray .Two coats of Brite Ceiling White are sufficient for an excellent finish.

COVERAGE **

On Primed surface	No of coats	Coverage
By brush /Roller application	2 coats	130-150 sq ft/ltr

**It depends on many factors like surface conditions, surface preparation, application skill, weather conditions, dilution etc. The coverage mentioned is under ideal conditions and will vary depending on site conditions.

TECHNICAL DATA:

1	Thinning	Potable Water	7	Flash Point	100% water –base paint, hence NA
2	Thinning Ratio	Maximum of 200-350ml of water per 1ltr of Paint.	8	Recommended Surface	Ceiling Surfaces
3	Method of application	Brush or Roller	9	Certification	As per IS 15489:2004 read with IS :101
4	Drying Time	SD : 30 minutes	10	Fire Hazard Class	Non - flammable
5	Pot life of thinned material	Use within 24hrs	11	Safety Data	Refer MSDS
6	Gloss Level	Matt Finish	12	VOC (gm/ltr)	12.0 gm/ltr

POINTS TO NOTE:

- Keep the container tightly closed to prevent drying.
- Shake well before use and do not over dilute.
- Please keep out of reach of children and away from foodstuff.
- In case of contact with eyes, wash immediately with water and seek medical advice.
- Use 1 or 2 coats of Bio –Wash for killing fungal growth
- For deeper shade apply 1 additional coat.

SPECIAL NOTE *

Before painting the following things should be checked thoroughly:

1. pH value of the wall surface (Ideal condition between 7-10).
2. Moisture content of the wall (Ideal condition –below 10-12%).

If these are violated, owner will be responsible.

*As per test conducted at Apollo R&D.

Version: APPL/01/2017.