



LIFE STYLE SILK

Premium Interior Emulsion

BEST IN CLASS Premium Interior Emulsion with soft egg shell sheen.

Apollo's **LIFE STYLE SILK Premium Interior Emulsion** is a best in class premium Interior Emulsion with Stain Proof properties.

USP: Rich Soft Egg Shell Finish, Stain Guard, Long Lasting Film, Fungus Resistant, extra Deep Colours, and High Washability.

Usage Area: Life Style silk emulsion is an interior wall finish that can be applied on all types of smooth plasters, false plasters,

false ceilings, asbestos sheets, concrete etc.

DIRECTIONS FOR USE:

Surface Preparation: Remove stains like mud, pencil marks, tea, coffee etc., with a mild detergent/ soap solutions. For harsh stains like pickles, oil, shoe polish, crayons, etc. Use turpentine.

To remove these stains use a piece of cloth or a sponge soaked in soap solution or turpentine and wipe over it. Then, immediately, wipe it with water to prevent stains from spreading. For best results, repeat both the actions 4-5 times. Moreover, do not allow stains to remain on your walls for a long time as they might become stubborn leading to incomplete removal. Do not use liquid bleach to clean stains as it might leave a discolored patch your walls.

Stain removal results may vary according to the nature for the stain.

Filling:

a).For **CRACKS:** For filling cracks up to 3mm use Apollo's INSTACARE CRACK LOCK.

b).For **HOLES & DENTS:** In case of dents and holes use Apollo's Wall grace putty or white cement and fine sand in the ratio 1:3.

Recommended Undercoats:

Option 1: For best performance, it is recommended to apply Life Style Premium interior emulsion as self priming with a thinning ratio of one part of paint with one part of water.

Option 2: Apply one coat of Apollo's " Instacare Seal O Prime High Performance Primer Sealer Interior & Exterior (Silicon enriched) as primer coat with a thinning ratio of one part of primer with one part of water.

Option 3: Apply one coat of Apollo's Aroprime Interior WT Primer with a thinning ratio of 1ltr of primer With 750ml water.

Top Coat: Apply 2 coats by diluting 1 litre of Apollo's Life Style Silk Premium Interior Emulsion with maximum 400ml of water. A gap of 4-6 hours should be given between coats. It can be applied by brush or roller or spray.

Maintenance Tips: For best performance ensure dry dust cleaning at regular intervals. Allow drying time of 3 weeks for proper film formation before any sponge cleaning with mild soap solution.

You finish, wipe the surface clean. Ensure drying time of one week for the paint before cleaning.

COVERAGE **

	No of coats	Coverage
On Primed surface		
By brush /Roller application	2 coats	130-150 sq ft/ltr

**It depends on many factors like surface conditions, surface preparation, application skill, weather conditions, dilution etc. The coverage mentioned is under ideal conditions and will vary depending on site conditions.

TECHNICAL DATA:

1	Thinning	Potable Water	7	Flash Point	100% water –base paint, hence NA
2	Thinning Ratio For Light /Pastel shades	Maximum of 500ml of water per 1ltr of Paint. Note: For Dark shades only maximum thinning should be 5-10% depending on shade. Coverage may be less as compared to light shades.	8	Recommended Surface	All types of smooth plasters, false ceilings, asbestos sheets, concrete etc.,
3	Method of application	Brush or Roller	9	Certification	As per IS 15489
4	Drying Time	SD :30 minutes	10	Fire Hazard Class	Non - flammable

5	Pot life of thinned material	Use within 24hrs	11	Safety Data	Refer MSDS
6	Gloss Level	8-16 @ 60 ⁰	12	VOC (gm/ltr)	30.0gm/ltr

POINTS TO NOTE:

- Keep the container tightly closed to prevent drying.
- Shake well before use and do not over dilute.
- Please keep out of reach of children and away from foodstuff.
- In case of contact with eyes, wash immediately with water and seek medical advice.
- Use 1 or 2 coats of Bio –Wash for killing fungal growth
- For deeper shade apply 1 additional coat.

SPECIAL NOTE *

Before painting the following things should be checked thoroughly:

1. pH value of the wall surface (Ideal condition between 7-10).
2. Moisture content of the wall (Ideal condition –below 10-12%).

If these are violated, owner will be responsible.

*As per test conducted at Apollo R&D.