



AROPEX

WONDER GUARD

Luxury exterior emulsion silicon enriched

Silicon Enriched Luxury Exterior Emulsion India's ONLY PRIMERLESS Waterproof Exterior Emulsion with 7 years Performance Warranty*.

Apollo's AROPEX WONDER GUARD Silicon Enriched Luxury Exterior Emulsion is a Water Repellent, Modified Acrylic, and Anti- Algal, Dirt Resistant wall finish.

USP: Thicker film build gives long lasting performance, Exceptional water repellence gives you freedom from dampness, Modified Acrylic , Anti-Algal , Dirt Resistant wall finish, Cutting edge technology for long lasting colour and excellent opacity, and Primerless –Hence, better adhesion with the walls & savings on Cost of Primer and its application.

Usage area: On exterior plastered surfaces.

DIRECTIONS FOR USE:

Cleaning: Ensure the plaster is completely dry and thoroughly clean, free from dust, flakes etc. For repainting surface with algae growth require thoroughly cleaning use Apollo's " Cleanex " diluted with equal quantity of water and apply with brush or roller . After 45 to 60 minutes wash with water so that surface is completely free from algae or any other growth .If the surface has the tendency of repeated algae growth use Apollo's " Bio –wash " diluted with equal volume of water and apply on surface which will inhibit further growth of algae.

Filling:

- a).For CRACKS: For filling cracks up to 3mm use Apollo's INSTACARE CRACK LOCK.
- b).For HOLES & DENTS: In case of dents and holes use Apollo's Wall grace putty or white cement and fine sand in the ratio 1:3.

Application on new surface: Directly apply two coat of Aropex Wonder guard without diluting with water. Apply third coat on horizontal surface for added protection. Avoid direct sunlight for better coverage.

Application on previously painted surface: Apply only one coat of Aropex Wonder guard without dilution, if the previously painted surface is of almost similar colour. In case of change in colour then add 200ml of water and apply two coats. Allow interval of 4 hrs between successive coats. Apply third coat horizontal surfaces for added protection.

Maintenance Tips: For better maintenance of the surface ensure proper cleaning of any algal or fungal growth at a regular interval of six months.

COVERAGE **

	No of coats	Coverage
On Primed surface		
By brush /Roller application	2 coats	45-50 sq ft/ltr

**It depends on many factors like surface conditions, surface preparation, application skill, weather conditions, dilution etc. The coverage mentioned is under ideal conditions and will vary depending on site conditions.

TECHNICAL DATA:

1	Thinning	Potable Water	8	Flash Point	100% water –base paint, hence NA
2	Thinning Ratio	No Dilution	9	Recommended Surface	Sand/cement plaster surface, asbestos, brickwork, concrete block, fiberboards
3	Thinning Ratio for Vibrant/Dark shades	No dilution	10	VOC (gm/ltr)	29.53 gm/ltr
4	Method of application	Brush or Roller	11	Certification	As per IS 15489:2004 read with IS :101
5	Drying Time	SD : 30-45 minutes	12	Fire Hazard Class	Non - flammable
6	Pot life of thinned material	Use within 24hrs	13	Safety Data	Refer MSDS
7	Gloss Level	1-6 @60° GH			

POINTS TO NOTE:

- Keep the container tightly closed to prevent drying.
- Shake well before use and do not over dilute.
- Please keep out of reach of children and away from foodstuff.
- In case of contact with eyes, wash immediately with water and seek medical advice.
- Use 1 or 2 coats of Bio –Wash for killing fungal growth
- For deeper shade apply 1 additional coat.

SPECIAL NOTE *

Before painting the following things should be checked thoroughly:

1. pH value of the wall surface (Ideal condition between 7-10).
2. Moisture content of the wall (Ideal condition –below 10-12%).

If these are violated, owner will be responsible.

*As per test conducted at Apollo R&D.

Version: APPL/01/2017.